

Podatkovni list proizvoda

Karakteristike

KBC10DMT21Z

Canalis – razvodna jedinica – 10 A – odabir faze – unaprijed ožičeno s GST18i3



Glavno

Range	Canalis
Product or component type	Tap-off unit
Product compatibility	KBA KBB KDP
Device application	Lighting Power socket distribution

Komplementarno

[Ue] rated operational voltage	230...400 V
[Ui] rated insulation voltage	400 V
[Ie] rated operational current	10 A at 35 °C
Network frequency	50/60 Hz
Protection type	Without protection
Electrical connection	Pre-wired with SO5Z1Z1-F - 3 x 1.5 mm ² for 0.5 m long - GST 18i3 female
Busbar trunking polarity	L1 + N + PE L2 + L1 + L3 + N + PE L2 + N2 + L3 + N3 + PE
Control type	Timer Impulse
Tap-off unit polarity	L1+L2 L1+L3 L1+N L2+L3 L2+N L2+N2 L3+N L3+N3
Tap-off unit connector type	With phase selection
Standards	EN/IEC 60439-2 EN/IEC 61439-6
Width	618 mm
Depth	30 mm
Height	76 mm
Colour	RAL 7035 : light grey
Product weight	85 g
Quantity per set	Set of 6

Okolina

IP degree of protection	IP55 conforming to EN/IEC 60529
-------------------------	---------------------------------

Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 1012 - Schneider Electric declaration of conformity	Compliant - since 1012 - Schneider Electric declaration of conformity
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poplunu analizu rizika, procjenu i ispitivanje specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Contractual warranty

Warranty period

18 months