

## KNA100DL4

Canalis–fleksibilni kut.držač rubni–100A–2D–unut/vanj  
kut od 80... 180°



### Glavno

Range of product	Canalis
Product name	KN
Product or component type	Elbow
Busbar description	Flexible elbow
Product compatibility	KN
Direction change type	2 dimensions
[Ie] rated operational current	100 A at 35 °C

### Komplementarno

Device application	Low power distribution
Thermal stress limit	8000 kA².s
Radiated magnetic field	186 pT
[Ue] rated operational voltage	230...500 V
[Uimp] rated impulse withstand voltage	6 kV
[Ui] rated insulation voltage	500 V
[Icw] rated short-time withstand current	2.8 kA
[Ipk] rated peak withstand current	14 kA
THDI	100 A at 0...15 % 80 A at 15...33 % 63 A at 33...100 %
Network frequency	50/60 Hz
Control type	Without
Number of circuits	1
Mounting mode	By screws
Standards	IEC 60439-2 IEC 61439-6
Operating angle	80...180 °
Length	355 mm
Colour	RAL 9001: white
Product weight	1.3 kg

### Okolina

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262
ambient air temperature for operation	0...35 °C without derating

### Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1012 - Schneider Electric declaration of conformity	Compliant - since 1012 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------