

KNA100EDF430

Canalis – Duž fleksibilnog dijela – 100 A – 3D – 3 m – za promjenu smjera



Glavno

Range of product	Canalis
Product name	KN
Product or component type	Busbar trunking
Busbar description	Flexible length
Product compatibility	KN
Direction change type	3 dimensions
[Ie] rated operational current	100 A at 35 °C

Komplementarno

Device application	Low power distribution
Thermal stress limit	8000 kA ² .s
Radiated magnetic field	186 pT
[Ue] rated operational voltage	230...500 V
[Uimp] rated impulse withstand voltage	6 kV
[Ui] rated insulation voltage	500 V
[Icw] rated short-time withstand current	2.8 kA
[Ipk] rated peak withstand current	14 kA
THDI	100 A at 0...15 % 80 A at 15...33 % 63 A at 33...100 %
Network frequency	50/60 Hz
Control type	Without
Number of circuits	1
Mounting mode	By screws
Standards	IEC 60439-2 IEC 61439-6
Length	3 m
Colour	RAL 9001: white
Product weight	5 kg

Okolina

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262
ambient air temperature for operation	0...35 °C without derating

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1012 - Schneider Electric declaration of conformity	Compliant - since 1012 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Contractual warranty

Warranty period	18 months
-----------------	-----------
