

## KNB32SG4

Canalis – razvodna jedinica za BS88 osigurač – A1 – 32 A s izolatorom



### Glavno

Range of product	Canalis
Range compatibility	Canalis KN
Product or component type	Tap-off unit
Product compatibility	Canalis KN busbar trunking with plug-in outlets
[Ie] rated operational current	32 A at 35 °C
Fuse type	Fuse isolator : for BS88 fuse, size A1 - conforming to BS standard
Provided equipment	Fuse to be ordered separately
Mounting mode	Plug-in with fixed polarity
Tap-off unit polarity	3L+N+PE 3L+PE
Colour	White RAL 9001

### Komplementarno

Device application	Low power distribution
[Ue] rated operational voltage	230...500 V depending on protective device
[Uimp] rated impulse withstand voltage	4.6 kV
[Ui] rated insulation voltage	500 V depending on protective device
Network frequency	50/60 Hz
Electrical connection	Cable clamp terminal - ISO50 - cable : 10 mm <sup>2</sup> flexible Cable clamp terminal - ISO50 - cable : 10 mm <sup>2</sup> rigid
Door opening side	Right
Tap-off unit disconnection mode	By opening the door
Standards	IEC 61439-1 IEC 61439-6
Width	344 mm
Depth	101 mm
Door opening size	432.5 mm
Height	165 mm
Product weight	1.5 kg

### Okolina

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

### Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1012 - Schneider Electric declaration of conformity	Compliant - since 1012 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------

