



Glavno

Range	TeSys
Device short name	LA1SK
Product or component type	Auxiliary contact block
Product compatibility	LC1SK
Auxiliary contacts operation	Instantaneous
Pole contact composition	1 NO + 1 NC
Connections - terminals	Screw clamp terminals 2 cable 1.5...4 mm ² - cable stiffness: solid Screw clamp terminals 1 cable 1.5...6 mm ² - cable stiffness: solid Screw clamp terminals 1 cable 0.5...6 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable 0.35...2.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 0.35...6 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable 0.35...1.5 mm ² - cable stiffness: flexible - without cable end

Komplementarno

Mounting location	Front side
[Ui] rated insulation voltage	690 V - conforming to BS 5424 690 V - conforming to IEC 60947 690 V - conforming to VDE 0110 group C 690 V - conforming to CSA C22.2 No 14
[Ue] rated operational voltage	690 V AC <= 400 Hz
[Ith] conventional free air thermal current	10 A at <= 55 °C
Associated fuse rating	IEC 60947 VDE 0660
Tightening torque	0.8 N.m - on screw clamp terminals
Width	27 mm
Product weight	0.022 kg

Okolina

standards	BS 5424 IEC 60947 NF C 63-110 VDE 0660
product certifications	CSA UL
IP degree of protection	IP2x
protective treatment	TC conforming to IEC 60068
ambient air temperature for operation	-20...50 °C
ambient air temperature for storage	-50...70 °C
operating altitude	2000 m without derating in temperature

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0718 - Schneider Electric declaration of conformity	Compliant - since 0718 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Available	Available
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------
