



Glavno

Range	Linergy
Product name	BW
Product or component type	Busbar support
Device short name	LA9Z
Quantity per set	Set of 10

Komplementarno

Range compatibility	TeSys
Poles description	3P
Permissible current	200 A with 12 x 5 mm busbar 250 A with 15 x 5 mm busbar 320 A with 20 x 5 mm busbar 400 A with 25 x 5 mm busbar 450 A with 30 x 5 mm busbar 360 A with 12 x 10 mm busbar 520 A with 20 x 10 mm busbar 630 A with 30 x 10 mm busbar
[Ui] rated insulation voltage	690 V conforming to IEC 60947-1 690 V conforming to NF C 20-040
Distance between supports	570 mm
Busbar pitch	60 mm
Colour	Grey

Okolina

IP degree of protection	IP20 with protective cover
temperature resistance	125 °C
standards	UL 508 IEC 61439-2
product certifications	IEC

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0626 - Schneider Electric declaration of conformity	Compliant - since 0626 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.