

Product data sheet  
Characteristics



LC2D09KUE

TeSys D reversing contactor - 3P -  $\leq 440$  V -  
9 A AC-3 - 100...250 V AC/DC coil





## Main

Range	TeSys
Product name	TeSys D Green
Product or component type	Reversing contactor
Device short name	LC2D
Contactor application	Motor control Resistive load
Utilisation category	AC-1 AC-3
Device presentation	Preassembled with reversing power busbar
Poles description	3P
Power pole contact composition	3 NO
[Ue] rated operational voltage	Power circuit <= 690 V AC 25...400 Hz
[Ie] rated operational current	9 A 60 °C) <= 440 V AC AC-3 power circuit 25 A 60 °C) <= 440 V AC AC-1 power circuit
Motor power kW	2,2 KW 220...230 V AC 50 Hz 4 KW 380...400 V AC 50 Hz 4 KW 415 V AC 50 Hz 4 KW 440 V AC 50 Hz 5,5 KW 500 V AC 50 Hz 5,5 kW 660...690 V AC 50 Hz
Motor power HP (UL / CSA)	0,33 Hp 115 V AC 60 Hz 1 phase 1 Hp 230/240 V AC 60 Hz 1 phase 2 Hp 200/208 V AC 60 Hz 3 phases 2 Hp 230/240 V AC 60 Hz 3 phases 5 Hp 460/480 V AC 60 Hz 3 phases 7,5 hp 575/600 V AC 60 Hz 3 phases
Control circuit type	AC 50/60 Hz AC/DC electronic DC AC/DC electronic
[Uc] control circuit voltage	100...250 V AC 50/60 Hz 100...250 V DC
Auxiliary contact composition	1 NO + 1 NC
[Uimp] rated impulse withstand voltage	6 kV IEC 60947
Overvoltage category	III
[Ith] conventional free air thermal current	10 A 60 °C signalling circuit 25 A 60 °C power circuit
Irms rated making capacity	250 A 440 V power circuit IEC 60947 140 A AC signalling circuit IEC 60947-5-1 250 A DC signalling circuit IEC 60947-5-1
Rated breaking capacity	250 A 440 V power circuit IEC 60947
[Icw] rated short-time withstand current	105 A 40 °C - 10 s power circuit 210 A 40 °C - 1 s power circuit 30 A 40 °C - 10 min power circuit 61 A 40 °C - 1 min power circuit 100 A - 1 s signalling circuit 120 A - 500 ms signalling circuit 140 A - 100 ms signalling circuit
Associated fuse rating	10 A gG signalling circuit IEC 60947-5-1 25 A gG <= 690 V type 1 power circuit 20 A gG <= 690 V type 2 power circuit
Average impedance	2,5 mOhm - Ith 25 A 50 Hz power circuit
[Ui] rated insulation voltage	Power circuit 690 V IEC 60947-4-1 Signalling circuit 690 V IEC 60947-1
Electrical durability	2,4 Mcycles 8 A AC-3 <= 440 V 0,6 Mcycles 25 A AC-1 <= 440 V
Power dissipation per pole	1,56 W AC-1 0,2 W AC-3
Front cover	With
Interlocking type	Mechanical

Mounting support	Plate Rail
Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 CSA C22.2 No 60947-4-1
Product certifications	CCC CSA EAC UL KC DNV-GL LROS (Lloyds register of shipping)
Connections - terminals	Power circuit screw clamp terminals 1 1... 4 mm <sup>2</sup> flexible without cable end Power circuit screw clamp terminals 2 1... 4 mm <sup>2</sup> flexible without cable end Power circuit screw clamp terminals 1 1... 4 mm <sup>2</sup> flexible with cable end Power circuit screw clamp terminals 2 1... 2,5 mm <sup>2</sup> flexible with cable end Power circuit screw clamp terminals 1 1... 4 mm <sup>2</sup> solid Power circuit screw clamp terminals 2 1... 4 mm <sup>2</sup> solid Control circuit screw clamp terminals 1 1... 4 mm <sup>2</sup> flexible without cable end Control circuit screw clamp terminals 2 1... 4 mm <sup>2</sup> flexible without cable end Control circuit screw clamp terminals 1 1... 4 mm <sup>2</sup> flexible with cable end Control circuit screw clamp terminals 2 1... 2,5 mm <sup>2</sup> flexible with cable end Control circuit screw clamp terminals 1 1... 4 mm <sup>2</sup> solid Control circuit screw clamp terminals 2 1... 4 mm <sup>2</sup> solid
Tightening torque	Power circuit 1,7 N.m screw clamp terminals flat Ø 6 mm Power circuit 1,7 N.m screw clamp terminals Philips No 2 Control circuit 1,7 N.m screw clamp terminals flat Ø 6 mm Control circuit 1,7 N.m screw clamp terminals Philips No 2
Operating time	45...55 ms closing 20...90 ms opening
Safety reliability level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1
Mechanical durability	15 Mcycles
Maximum operating rate	3600 cyc/h 60 °C

## Complementary

Coil technology	Built-in bidirectional peak limiting
Control circuit voltage limits	<= 0.1 Uc -40...70 °C drop-out AC/DC 0.85...1.1 Uc -40...60 °C operational AC/DC 1...1.1 Uc 60...70 °C operational AC/DC
Inrush power in VA	25 VA 50/60 Hz 20 °C)
Inrush power in W	18 W 20 °C
Hold-in power consumption in VA	1,6 VA 20 °C) 50/60 Hz
Hold-in power consumption in W	1,1 W 20 °C
Heat dissipation	1,1 W 50/60 Hz
Auxiliary contacts type	Mechanically linked 1 NO + 1 NC IEC 60947-5-1 Mirror contact 1 NC IEC 60947-4-1
Signalling circuit frequency	25...400 Hz
Minimum switching current	5 mA signalling circuit
Minimum switching voltage	17 V signalling circuit

Non-overlap time	1,5 Ms on de-energisation between NC and NO contact 1,5 ms on energisation between NC and NO contact
Insulation resistance	> 10 MOhm signalling circuit
Compatibility code	LC2D

## Environment

IP degree of protection	IP20 front face IEC 60529
Protective treatment	TH IEC 60068-2-30
Pollution degree	3
Ambient air temperature for operation	-40...60 °C 60...70 °C with derating
Ambient air temperature for storage	-60...80 °C
Operating altitude	0...3000 m
Fire resistance	850 °C IEC 60695-2-1
Flame retardance	V1 UL 94
Mechanical robustness	Vibrations contactor open2 Gn, 5...300 Hz Vibrations contactor closed4 Gn, 5...300 Hz Shocks contactor open10 Gn for 11 ms Shocks contactor closed15 Gn for 11 ms
Maksimalna visina	77 mm
Maksimalna širina	90 mm
Maksimalna dubina	86 mm
Neto težina	0,783 kg
Colour	Sivo SE GREY 6) Green SE GREEN 2)

## Offer Sustainability

Status održive ponude	Proizvod Green Premium
Uredba REACH	 <a href="#">Izjava REACH</a>
Direktiva EU RoHS	Sukladno  <a href="#">Izjava EU RoHS</a>
Bez žive	Da
Informacije o RoHS izuzeću	 <a href="#">Da</a>
Propis RoHS za Kinu	 <a href="#">Izjava RoHS Za Kinu</a>
Izjava o očuvanju okoliša	 <a href="#">Ekološki Profil Proizvoda</a>
Profil cirkularnosti	 <a href="#">Informacije O Kraju Vijeka Trajanja</a>
WEEE	Proizvod se na tržištima EU mora odlagati u skladu sa specifičnim propisima o prikupljanju otpada; nikako se ne smije odlagati s komunalnim otpadom.
Halogeni elementi	Plastični dijelovi i kabeli bez halogenih elemenata

## Contractual warranty

Jamstvo	18 months
---------	-----------