



Glavno

Range	Linergy
Product name	Linergy DS
Product or component type	Distribution block

Komplementarno

Mounting support	DIN rail
Range compatibility	Prisma - G Prisma - P Pragma Compact Prisma - PH Prisma - Pack Spacial Kaedra TeSys
Product compatibility	Spacial enclosures
Poles description	4P
Distribution block outgoers	4 x 7 holes
[Ue] rated operational voltage	230 V AC (Ph/N) 440 V AC (Ph/Ph)
[Ui] rated insulation voltage	500 V AC
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	100 A at 40 °C
[Icw] rated short-time withstand current	3 kA 1 s
[Ipk] rated peak withstand current	24 kA
Connections - terminals	Supply: screw terminal, 2 x 2.5...25 mm ² (rigid) Supply: screw terminal, 2 x 1.5...16 mm ² (flexible) with cable end Distribution: screw terminal, 5 x 1.5...10 mm ² (flexible) with cable end Distribution: screw terminal, 5 x 1.5...16 mm ² (rigid)
Tightening torque	Supply: Ø7.5 mm, 2 N.m with flat screwdriver Supply: Ø7.5 mm, 2 N.m with PZ2 screwdriver Distribution: Ø5.5 mm, 2 N.m with flat screwdriver Distribution: Ø5.5 mm, 2 N.m with PZ2 screwdriver
9 mm pitches	8
Height	100 mm
Width	71 mm
Depth	50.5 mm
Product weight	0.21 kg
Colour	White RAL 9003

Okolina

pollution degree	3
overvoltage category	III
dielectric strength	2500 V
standards	EN/IEC 60947-7-1

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

EN/IEC 61439-1

ambient air temperature for operation

-25...55 °C

Offer Sustainability

Not Green Premium product

Not Green Premium product

Compliant - since 1250 - Schneider Electric declaration of conformity

Compliant - since 1250 - Schneider Electric declaration of conformity
