



## Glavno

Range	Linergy
Product name	Linergy DS
Product or component type	Distribution block

## Komplementarno

Mounting support	DIN rail
Range compatibility	Prisma - G Prisma - P Prigma Compact Prisma - PH Prisma - Pack Spacial Kaedra TeSys
Product compatibility	Spacial enclosures
Poles description	4P
Distribution block outgoers	4 x 15 holes
[Ue] rated operational voltage	230 V AC (Ph/N) 440 V AC (Ph/Ph)
[Ui] rated insulation voltage	500 V AC
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	125 A at 40 °C
[Icw] rated short-time withstand current	4.2 kA 1 s
[Ipk] rated peak withstand current	28 kA
Connections - terminals	Supply: screw terminal, 1 x 10...35 mm <sup>2</sup> (rigid) Supply: screw terminal, 1 x 6...35 mm <sup>2</sup> (flexible) with cable end Distribution: screw terminal, 3 x 4...25 mm <sup>2</sup> (flexible) with cable end Distribution: screw terminal, 11 x 1.5...16 mm <sup>2</sup> (rigid) Distribution: screw terminal, 11 x 1.5...10 mm <sup>2</sup> (flexible) with cable end Distribution: screw terminal, 3 x 6...35 mm <sup>2</sup> (rigid)
Tightening torque	Distribution: Ø6.5 mm, 2 N.m with flat screwdriver Distribution: Ø6.5 mm, 2 N.m with PZ2 screwdriver Supply: Ø9.5 mm, 2.5 N.m with flat screwdriver Supply: Ø9.5 mm, 2.5 N.m with PZ2 screwdriver Distribution: Ø8.5 mm, 2 N.m with flat screwdriver Distribution: Ø8.5 mm, 2 N.m with PZ2 screwdriver
9 mm pitches	18
Height	100 mm
Width	162 mm
Depth	50.5 mm
Product weight	0.562 kg
Colour	White RAL 9003

## Okolina

pollution degree	3
------------------	---

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.  
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.  
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i popunivu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.  
Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

overvoltage category	III
dielectric strength	2500 V
standards	EN/IEC 60947-7-1 EN/IEC 61439-1
ambient air temperature for operation	-25...55 °C

### Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 1250 - Schneider Electric declaration of conformity	Compliant - since 1250 - Schneider Electric declaration of conformity