



## Glavno

Range	Lineryy
Product name	Lineryy DS
Product or component type	Distribution block

## Komplementarno

Mounting support	DIN rail
Range compatibility	Prisma - G Prisma - P Prigma Prisma - PH Prisma - Pack Spacial Kaedra TeSys
Product compatibility	Spacial enclosures
Poles description	4P
Distribution block outgoers	4 x 12 holes
[Ue] rated operational voltage	230 V AC (Ph/N) 440 V AC (Ph/Ph)
[Ui] rated insulation voltage	500 V AC
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	160 A at 40 °C
[Icw] rated short-time withstand current	8.4 kA 1 s
[Ipk] rated peak withstand current	36 kA
Connections - terminals	Distribution: screw terminal, 3 x 10...35 mm <sup>2</sup> (rigid) Distribution: screw terminal, 3 x 4...25 mm <sup>2</sup> (flexible) with cable end Distribution: screw terminal, 8 x 2.5...25 mm <sup>2</sup> (rigid) Distribution: screw terminal, 8 x 1.5...16 mm <sup>2</sup> (flexible) with cable end Supply: screw terminal, 1 x 25...70 mm <sup>2</sup> (rigid) Supply: screw terminal, 1 x 16...50 mm <sup>2</sup> (flexible) with cable end
Tightening torque	Distribution: Ø7.5 mm, 2 N.m with flat screwdriver Distribution: Ø7.5 mm, 2 N.m with PZ2 screwdriver Supply: Ø12 mm, 5 N.m with flat screwdriver Supply: Ø12 mm, 5 N.m with PZ2 screwdriver Distribution: Ø9 mm, 2.5 N.m with flat screwdriver Distribution: Ø9 mm, 2.5 N.m with PZ2 screwdriver
9 mm pitches	20
Height	100 mm
Width	174 mm
Depth	50.5 mm
Product weight	0.557 kg
Colour	White RAL 9003

## Okolina

pollution degree	3
overvoltage category	III

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.  
 Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.  
 Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.  
 Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu sadržanih informacija.

---

dielectric strength	2500 V
standards	EN/IEC 60947-7-1 EN/IEC 61439-1
ambient air temperature for operation	-25...55 °C

---

### Offer Sustainability

---

Not Green Premium product	Not Green Premium product
Compliant - since 1250 - Schneider Electric declaration of conformity	Compliant - since 1250 - Schneider Electric declaration of conformity

---