



Glavno

Range	Lineryg
Product name	Lineryg DS
Product or component type	Extension module
Comb busbar, distribution terminal block accessory type	Neutral bar
Poles description	1N
Accessory / separate part category	Connection accessories

Komplementarno

Distribution block outgoers	15 holes
Mounting support	Direct mounting on rear
Mounting mode	By screws
[Ue] rated operational voltage	230 V AC (Ph/N)
[Ie] rated operational current	125 A at 40 °C
[Ui] rated insulation voltage	500 V AC
[Uimp] rated impulse withstand voltage	8 kV conforming to EN/IEC 61439-1
[Icw] rated short-time withstand current	3.5 kA 1 s
[Ipk] rated peak withstand current	20 kA
Busbar length	155 mm
9 mm pitches	17
18 mm pitches	8.5
Height	20 mm
Width	155 mm
Depth	35 mm
Product weight	149 g
Connections - terminals	Supply: screw terminal, 1 x 10...35 mm ² (rigid) Supply: screw terminal, 1 x 6...35 mm ² (flexible) with cable end Distribution: screw terminal, 3 x 10...35 mm ² (rigid) Distribution: screw terminal, 3 x 4...25 mm ² (flexible) with cable end Distribution: screw terminal, 11 x 1.5...16 mm ² (rigid) Distribution: screw terminal, 11 x 1.5...10 mm ² (flexible) with cable end
Tightening torque	Distribution: Ø6.5 mm, 2 N.m with flat screwdriver Distribution: Ø6.5 mm, 2 N.m with PZ2 screwdriver Supply: Ø9.5 mm, 2.5 N.m with flat screwdriver Supply: Ø9.5 mm, 2.5 N.m with PZ2 screwdriver Distribution: Ø8.5 mm, 2 N.m with flat screwdriver Distribution: Ø8.5 mm, 2 N.m with PZ2 screwdriver
Range compatibility	Compact

Okolina

standards	EN/IEC 61439-1 IEC 60947-7-1 IEC 61439-2
pollution degree	3
overvoltage category	III
dielectric strength	2500 V
ambient air temperature for operation	-25...55 °C
colour	White (RAL 9003)

Informacije dane u ovoj dokumentaciji sadrže opće i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Offer Sustainability

Not Green Premium product

Not Green Premium product

Compliant - since 1250 - Schneider Electric declaration of conformity Compliant - since 1250 - Schneider Electric declaration of conformity
