



## Glavno

Range	EasyPact
Product name	EasyPact TVS
Product or component type	Differential thermal overload relay
Device short name	LRE
Relay application	Motor protection
Phase failure sensitivity	Tripping current 130 % of Ir on two phase, the last one at 0 conforming to IEC 60947-4-1
Colour	Grey RAL 7011

## Komplementarno

Product compatibility	LC1E06...38
Network type	AC
Network frequency	50...60 Hz
Mounting support	Under contactor Plate (with specific accessories) Rail (with specific accessories)
Thermal overload class	Class 10A conforming to IEC 60947-4-1
Signalling function	Relay trip indicator
Thermal protection adjustment range	1...1.6 A
Tripping threshold	1.14 +/- 0.06 Ir conforming to IEC 60947-4-1
Mechanical robustness	Shocks: 6 Gn for 11 ms conforming to IEC 60068-2-7 Vibrations: 3 Gn conforming to IEC 60068-2-6
Auxiliary contact composition	1 NO + 1 NC
[Ith] conventional free air thermal current	Signalling circuit: 5 A
[Ue] rated operational voltage	<= 690 V AC
Associated fuse rating	Power circuit: 4 A (gG) Power circuit: 2 A (aM) Signalling circuit: 5 A (gG)
[Ui] rated insulation voltage	690 V conforming to IEC 60947-4-1
[Uimp] rated impulse withstand voltage	6 kV
Local signalling	Trip indicator
Control type	Stop: red push-button Reset: green push-button
Temperature compensation	-20...60 °C
Connections - terminals	Screw clamp terminals (power circuit): 1 flexible cable(s) without cable end of 1.5...6 mm <sup>2</sup> Screw clamp terminals (power circuit): 1 flexible cable(s) with cable end of 1...4 mm <sup>2</sup> Screw clamp terminals (power circuit): 1 solid cable(s) without cable end of 1...6 mm <sup>2</sup> Screw clamp terminals (signalling circuit): 2 flexible cable(s) without cable end of 1...2.5 mm <sup>2</sup> Screw clamp terminals (signalling circuit): 2 flexible cable(s) with cable end of 1...2.5 mm <sup>2</sup> Screw clamp terminals (signalling circuit): 2 solid cable(s) without cable end of 1...2.5 mm <sup>2</sup>
Tightening torque	Power circuit (screw clamp terminals): 1.7 N.m Signalling circuit (screw clamp terminals): 1.7 N.m
Height	44.5 mm
Width	45 mm
Depth	70 mm

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Product weight 0.13 kg

---

## Okolina

standards	IEC 60947-4-1 IEC 60947-5-1
product certifications	GOST
protective treatment	TH conforming to IEC 60068
IP degree of protection	IP20 conforming to IEC 60529
ambient air temperature for operation	-20...70 °C with derating -20...60 °C without derating conforming to IEC 60947-4-1
ambient air temperature for storage	-60...80 °C
fire resistance	850 °C conforming to IEC 60068-2-1
dielectric strength	6 kV at 50 Hz conforming to IEC 60255-5
electromagnetic compatibility	Surge withstand: 6 kV conforming to IEC 60801-5

## Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1110 - Schneider Electric declaration of conformity	Compliant - since 1110 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations