

## LTMR27CFM

kontroler za motor LTMR TeSys T – 100..240 V AC  
27 A za CANopen



### Glavno

Range	TeSys
Product name	TeSys T
Device short name	LTMR
Product or component type	Motor controller
Device application	Equipment monitoring and control
Measurement current	1.35...27 A
[Us] rated supply voltage	100...240 V AC 50/60 Hz
Current consumption	8...62.8 mA
Supply voltage limits	93.5...264 V AC
Communication port protocol	CANopen
Bus type	CANopen ISO 1198 interface, addressing 1...127, transmission rate 10...1000 kbit/s, SUB-D 9 with 4 twisted shielded pairs cable CANopen ISO 1198 interface, addressing 1...127, transmission rate 10...1000 kbit/s, terminal block with 4 twisted shielded pairs cable

### Komplementarno

[Ui] rated insulation voltage	690 V conforming to UL 508 690 V conforming to CSA C22.2 No 14 690 V conforming to EN/IEC 60947-1
[Uimp] rated impulse withstand voltage	4 kVfor supply, inputs and outputs conforming to EN/IEC 60947-4-1 6 kVfor current or voltage measurement circuit conforming to EN/IEC 60947-4-1 0.8 kVfor communication circuit conforming to EN/IEC 60947-4-1
Short-circuit withstand	100 kA conforming to EN/IEC 60947-4-1
Associated fuse rating	0.5 A gGfor control circuit 4 A gGfor output
Protection type	Earth-leakage protection Phase failure Reverse polarity protection Thermal overload protection Thermal protection Overload Phase unbalance Locked rotor Overload (long time) Load fluctuation Power factor variation
Network and machine diagnosis type	Phase fault and earth fault trip counters Remaining operating time before overload tripping Running hours counter/operating time Starting current and time Waiting time after overload tripping Fault recording Event recording Trip context information Trip history information Motor control command recording
Logic input number	6
Input current	3.1 mA at 100 V 7.5 mA at 240 V
Current state 0 guaranteed	Logic input : 0...40 V and <= 15 mA for 25 ms
Current state 1 guaranteed	Logic input : 79...264 V and >= 2 mA for 25 ms
Maximum operating frequency	2 Hz

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poipunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Load current	5 A at 250 V AC for logic output 5 A at 30 V DC for logic output
Permissible power	480 VA (AC-15), $I_e = 2$ A, 500000 cycles (output) 30 W (DC-13), $I_e = 1.25$ A, 500000 cycles (output)
Operating rate	1800 cyc/h
Contacts type and composition	1 NO + 1 NC fault signal 3 NO
Metering type	Earth-fault current Phase current I1, I2, I3 RMS Temperature Average current $I_{avg}$ Imbalance current
Measurement accuracy	+/- 30 min/year internal clock 0,02 temperature 5...15 % earth fault current internal measurement (for current > 0.2 A) 1 % current 1 % voltage (100...830 V) 5 % active and reactive power 5 % earth fault current external measurement (< 5 % or 0.01 A) 3 % power factor ( $\cos \phi > 0.6$ )
Overvoltage category	III
Connection pitch	5.08 mm
Connections - terminals	Connector, 1 flexible cable with cable end 0.25...2.5 mm <sup>2</sup> /AWG 24...AWG 14 for control circuit Connector, 1 flexible cable without cable end 0.2...2.5 mm <sup>2</sup> /AWG 24...AWG 14 for control circuit Connector, 1 flexible cable without cable end 0.25...2.5 mm <sup>2</sup> /AWG 24...AWG 14 for control circuit Connector, 1 solid cable without cable end 0.2...2.5 mm <sup>2</sup> /AWG 24...AWG 14 for control circuit Connector, 2 flexible cable with cable end 0.2...1 mm <sup>2</sup> /AWG 24...AWG 14 for control circuit Connector, 2 flexible cable without cable end 0.2...1.5 mm <sup>2</sup> /AWG 24...AWG 14 for control circuit Connector, 2 flexible cable without cable end 0.5...1.5 mm <sup>2</sup> /AWG 24...AWG 14 for control circuit Connector, 2 solid cable without cable end 0.2...1 mm <sup>2</sup> /AWG 24...AWG 14 for control circuit
Tightening torque	0.5...0.6 N.m, 3 mm flat screwdriver for control circuit
Pollution degree	3
Electromagnetic compatibility	<ul style="list-style-type: none"> <li>● electrostatic discharge 3 (8 kV air, 6 kV contact), conforming to EN/IEC 61000-4-2</li> <li>● fast transients immunity test other circuits level 3 (2 kV), conforming to EN/IEC 61000-4-4</li> <li>● fast transients immunity test on supply and relay outputs level 4 (4 kV), conforming to EN/IEC 61000-4-4</li> <li>● conducted RF disturbances (10 V), conforming to EN/IEC 61000-4-6</li> <li>● surges serial mode (1 kV) control circuit, conforming to EN/IEC 61000-4-5</li> <li>● surges common mode (2 kV) communication, conforming to EN/IEC 61000-4-5</li> <li>● surges common mode (2 kV) control circuit, conforming to EN/IEC 61000-4-5</li> <li>● radiated RF fields 3 (10 V/m), conforming to EN/IEC 61000-4-3</li> <li>● voltage dips and interruptions immunity test (70 %, 500 ms), conforming to EN/IEC 61000-4-11</li> <li>● surges serial mode (0.5 kV) temperature sensor, conforming to EN/IEC 61000-4-5</li> <li>● surges common mode (1 kV) temperature sensor, conforming to EN/IEC 61000-4-5</li> <li>● surges serial mode (2 kV) relay outputs and supply, conforming to EN/IEC 61000-4-5</li> <li>● surges common mode (4 kV) relay outputs and supply, conforming to EN/IEC 61000-4-5</li> </ul>
Width	91 mm
Height	61 mm
Depth	122.5 mm
Product weight	0.53 kg
Web services	Web server
Compatibility code	LTMR

## Okolina

standards	EN 60947-4-1 IACS E10 IEC 60947-4-1
-----------	---

product certifications	ABS ATEX BV CCC CSA C-Tick DNV GL KERI LROS (Lloyds register of shipping) NOM RINA RMRoS UL EAC
protective treatment	12 x 24 hour cycles conforming to EN/IEC 60068-2-30 48 h conforming to EN/IEC 60070-2-11 TH conforming to EN/IEC 60068
fire resistance	650 °C conforming to EN/IEC 60695-2-12 960 °C conforming to UL 94
ambient air temperature for operation	-20...60 °C
ambient air temperature for storage	-40...80 °C
operating altitude	<= 2000 m without derating
mechanical robustness	<ul style="list-style-type: none"> <li>• shocks half sine wave acceleration (15 Gn for 11 ms) conforming to EN/IEC 60068-2-27</li> <li>• vibrations mounted on symmetrical rail (1 Gn, 5...300 Hz) conforming to EN/IEC 60068-2-6</li> <li>• vibrations plate mounted (4 Gn, 5...300 Hz) conforming to EN/IEC 60068-2-6</li> </ul>
IP degree of protection	IP20

### Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0501 - Schneider Electric declaration of conformity	Compliant - since 0501 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available

### Contractual warranty

Warranty period	18 months
-----------------	-----------