

LU2MB0ES

blok za prekretanje LU2M – 32 A – 48 V DC/AC
50...60 Hz – izravna montaža



Glavno

Range	TeSys
Device short name	LU2MB
Product or component type	Reverser block

Komplementarno

Mounting mode	Plug-in
[Ue] rated operational voltage	230 V 440 V 500 V 690 V
Network frequency	40...60 Hz
Inrush restraint duration	15 ms for DC network 25 ms for AC network 50/60 Hz
Operating time	150 ms with change of direction 75 ms without change of direction
[Uc] control circuit voltage	48 V AC 48...72 V DC
Current consumption	2300 mA at 48...72 V AC I maximum while closing 2300 mA at 48...72 V DC I maximum while closing
[Ui] rated insulation voltage	600 V conforming to UL 509 690 V conforming to IEC 60947-2 600 V conforming to CSA C22.2 No 15
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-6-2
Connections - terminals	Control circuit: screw clamp terminals 1 cable 0.34...1.5 mm ² - external diameter: 3 mm - cable stiffness: flexible - with cable end Control circuit: screw clamp terminals 1 cable 0.75...1.5 mm ² - external diameter: 3 mm - cable stiffness: flexible - without cable end Control circuit: screw clamp terminals 1 cable 0.75...1.5 mm ² - external diameter: 3 mm - cable stiffness: rigid - without cable end Control circuit: screw clamp terminals 2 cable 0.34...1.5 mm ² - external diameter: 3 mm - cable stiffness: flexible - with cable end Control circuit: screw clamp terminals 2 cable 0.75...1.5 mm ² - external diameter: 3 mm - cable stiffness: flexible - without cable end Control circuit: screw clamp terminals 2 cable 0.75...1.5 mm ² - external diameter: 3 mm - cable stiffness: rigid - without cable end Power circuit: screw clamp terminals 1 cable 1...10 mm ² - external diameter: 4 mm - cable stiffness: rigid - without cable end Power circuit: screw clamp terminals 1 cable 1...6 mm ² - external diameter: 4 mm - cable stiffness: flexible - with cable end Power circuit: screw clamp terminals 1 cable 2.5...10 mm ² - external diameter: 4 mm - cable stiffness: flexible - without cable end Power circuit: screw clamp terminals 2 cable 1...6 mm ² - external diameter: 4 mm - cable stiffness: flexible - with cable end Power circuit: screw clamp terminals 2 cable 1...6 mm ² - external diameter: 4 mm - cable stiffness: rigid - without cable end Power circuit: screw clamp terminals 2 cable 1.5...6 mm ² - external diameter: 4 mm - cable stiffness: flexible - without cable end
Tightening torque	Control circuit: 0.8...1.2 N.m - with screwdriver 5 mm flat Power circuit: 1.9...2.5 N.m - with screwdriver 6 mm flat Power circuit: 1.9...2.5 N.m - with screwdriver 6 mm Philips No 2 Control circuit: 0.8...1.2 N.m - with screwdriver 5 mm Philips No 2
Product weight	0.4 kg

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanosti, poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Okolina

standards	EN 60947-6-3 IEC 60947-6-3 UL 508 type E with phase barrier CSA C22.2 No 14 type E
product certifications	ABS ASEFA ATEX BV CCC CSA DNV GL GOST LROS (Lloyds register of shipping) UL
IP degree of protection	IP20 front panel and wired terminals conforming to IEC 60947-1 IP20 other faces conforming to IEC 60947-1 IP40 front panel outside connection zone conforming to IEC 60947-1
protective treatment	TH conforming to IEC 60068
ambient air temperature for operation	-25...60 °C with LUCM -25...70 °C with LUCA, LUCB, LUCC, LUCD
ambient air temperature for storage	-40...85 °C
fire resistance	650 °C conforming to IEC 60695-2-12 960 °C parts supporting live components conforming to IEC 60695-2-12
operating altitude	2000 m
shock resistance	10 gn power poles open conforming to IEC 60068-2-27 15 gn power poles closed conforming to IEC 60068-2-27
vibration resistance	2 gn 5...300 Hz power poles open conforming to IEC 60068-2-27 4 gn 5...300 Hz power poles closed conforming to IEC 60068-2-27
resistance to electrostatic discharge	8 kV level 3, in open air conforming to IEC 61000-4-2 8 kV level 4, on contact conforming to IEC 61000-4-2
resistance to radiated fields	10 V/m level 3 conforming to IEC 61000-4-3
resistance to fast transients	2 kV class 3 serial link conforming to IEC 61000-4-4 4 kV class 4 all circuits except for serial link conforming to IEC 61000-4-4
non-dissipating shock wave	1 kV serial mode conforming to IEC 60947-6-2 2 kV common mode conforming to IEC 60947-6-2
immunity to radioelectric fields	10 V conforming to IEC 61000-4-6

Contractual warranty

Warranty period	18 months
-----------------	-----------