



## Glavno

Range	Linergy
Product name	BZ
Device short name	LA9Z
Product or component type	Adaptors for busbar systems
Number of ways	1 way

## Komplementarno

Range compatibility	Prisma - G Prisma - P Compact Prisma - PH Spacial
Product compatibility	NSX400...630 PowerPact NL
Poles description	3P
Permissible current	200 A with 12 x 5 mm busbar 250 A with 15 x 5 mm busbar 320 A with 20 x 5 mm busbar 400 A with 25 x 5 mm busbar 450 A with 30 x 5 mm busbar 360 A with 12 x 10 mm busbar 520 A with 20 x 10 mm busbar 630 A with 30 x 10 mm busbar
[U <sub>i</sub> ] rated insulation voltage	690 V
Busbar pitch	60 mm
Width	139 mm
Height	270 mm
Depth	63 mm
Colour	Anthracite grey

## Okolina

IP degree of protection	IP20 conforming to IEC 60529
-------------------------	------------------------------

## Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1121 - Schneider Electric declaration of conformity	Compliant - since 1121 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.