



Glavno

Range	Fupact
Product or component type	Block of 3 current transformers
Device application	Power supply
Range compatibility	Fupact ISFL - ISFL160
Poles description	3P
Current transformer ratio	150/5 A
Power consumption in VA	1.5 VA

Komplementarno

Accessory / separate part category	Measurement accessory
Current transformer type	Measurement class 1
Safety factor	<= 5
[Ue] rated operational voltage	800 V AC at 50/60 Hz
IP degree of protection	IP20
Standards	BS 7626 IEC 60044-1 VDE 0414
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...80 °C
Height	328.5 mm
Width	49.5 mm
Depth	30 mm

Okolina

Offer Sustainability

Not Green Premium product	Not Green Premium product
---------------------------	---------------------------

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.