



Glavno

| | |
|---|--|
| Range of product | EasyPact CVS400...630 |
| Range | EasyPact |
| Product name | EasyPact CVS |
| Device short name | Vigi CVS630NA |
| Product or component type | Earth leakage switch disconnecter |
| Device application | Distribution |
| Poles description | 4P |
| Network type | AC |
| [Ie] rated operational current | 630 A AC-22A: AC 50/60 Hz 380/415 V 500 A AC-23A: AC 50/60 Hz 380/415 V 500 A AC-23A: AC 50/60 Hz 220/240 V 500 A AC-23A: AC 50/60 Hz 440 V 630 A AC-22A: AC 50/60 Hz 220/240 V 630 A AC-22A: AC 50/60 Hz 440 V |
| [Ith] conventional free air thermal current | 600 A (50 °C) |
| [Icm] rated short-circuit making capacity | 105 kA with upstream protection circuit breaker 8.5 kA switch-disconnector alone |
| Breaking capacity code | NA |
| Suitability for isolation | Yes conforming to EN 60947-3 Yes conforming to IEC 60947-3 |
| Utilisation category | AC-22A AC-23A |
| Earth-leakage add-on module name | MH |
| Earth-leakage protection | With |

Komplementarno

| | |
|--|--|
| Network frequency | 50/60 Hz |
| Control type | Toggle |
| Mounting mode | Fixed |
| Mounting support | Backplate |
| Upside connection | Front |
| Downside connection | Front |
| [Icw] rated short-time withstand current | 2.32 kA (20 s) conforming to IEC 60947-3 6 kA (1 s) conforming to IEC 60947-3 6 kA (3 s) conforming to IEC 60947-3 |
| Contact position indicator | Yes |
| Visible break | No |
| Residual earth-leakage sensitivity adjustment type | Adjustable 5 settings |
| [IΔn] residual earth-leakage sensitive adjustment | 0.03 A 0.3 A 1 A 10 A 3 A |
| Residual earth-leakage time delay adjustment type | Adjustable 4 settings |
| [Δt] residual earth-leakage time delay adjustment | 0 ms 150 ms 310 ms 60 ms |
| Mechanical durability | 15000 cycles conforming to IEC 60947-3 |

Informacije dane u ovoj dokumentaciji sadrže opće opterećenje i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

| | |
|-----------------------|--|
| Electrical durability | 2500 cycles conforming to IEC 60947-3 415 V In AC 50/60 Hz AC-22A: 2500 cycles conforming to IEC 60947-3 415 V In AC 50/60 Hz AC-23A: |
| Connection pitch | 45 mm |
| Height | 355 mm |
| Width | 185 mm |
| Depth | 110 mm |

Okolina

| | |
|---------------------------------------|-----------------------------|
| standards | EN 60947-3 IEC 60947-3 |
| product certifications | GOST IEC |
| electrical shock protection class | Class II |
| pollution degree | 3 conforming to IEC 60664-1 |
| ambient air temperature for operation | -25...70 °C |
| ambient air temperature for storage | -50...85 °C |

Offer Sustainability

| | |
|---|---|
| Green Premium product | Green Premium product |
| Compliant - since 1041 - Schneider Electric declaration of conformity | Compliant - since 1041 - Schneider Electric declaration of conformity |
| Reference not containing SVHC above the threshold | Reference not containing SVHC above the threshold |
| Available | Available |
| Available | Available |