



### Glavno

Range	TeSys
Product or component type	Contacteur coil
Device short name	LX1D2
Control circuit type	AC 50/60 Hz
[Uc] control circuit voltage	48 V AC 50/60 Hz
Average resistance	25 Ohm at 20 °C
Inductance of closed circuit	1 H
Product compatibility	LC1D09...D18

### Komplementarno

Coil technology	Without built-in suppressor module
Control circuit voltage limits	0.8...1.1 Uc at <= 55 °C operational 50/60 Hz
Inrush power in VA	70 VA at 20 °C (cos f 0.75) 50/60 Hz
Hold-in power consumption in VA	8 VA at 20 °C (cos f 0.3) 50/60 Hz

### Okolina

product weight	0.7 kg
----------------	--------

### Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0702 - Schneider Electric declaration of conformity	Compliant - since 0702 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poplunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.