



Glavno

Range	PowerLogic
Product name	PowerLogic PM3000
Device short name	PM3210
Product or component type	Power meter

Komplementarno

Power quality analysis	Up to the 15th harmonic
Device application	Power monitoring Sub billing Multi-tariff
Type of measurement	Voltage Current Frequency Power factor Apparent power Energy Active and reactive power Total current harmonic distortion THD (I) Total voltage harmonic distortion THD (U)
[Us] rated supply voltage	100...300 V DC 100...277 V AC (45...65 Hz) 173...480 V AC (45...65 Hz)
Network frequency	50 Hz 60 Hz
[In] rated current	1 A 5 A
Poles description	1P + N 3P 3P + N
Power consumption in VA	5 VA
Display type	Backlit LCD
Display resolution	128 x 96 pixels
Sampling rate	32 samples/cycle
Measurement current	0.05...6 A 0.02...1.2 A
Analogue input type	Current 0...5 A Current 0...1 A
Measurement voltage	50...330 V AC 45...65 Hz direct 50...330 V AC 45...65 Hz phase to neutral 80...570 V AC 45...65 Hz direct 80...570 V AC 45...65 Hz phase to phase 570...999000 V AC 45...65 Hz with external VT
Frequency measurement range	45...65 Hz
Number of inputs	0
Measurement accuracy	0.3 % current (0.5...6 A) 0.5 % current (0.1...1.2 A) 0.3 % voltage (50...330 V) 0.3 % voltage (80...570 V)
Accuracy class	Class 0.5S (active energy according to IEC 62053-22)

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poplunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Class 2 (reactive energy according to IEC 62053-23)
 Class 1 (active energy according to IEC 62053-21)
 Class C (active energy according to EN 50470-3)

Number of outputs	1 pulse
Information displayed	Tariff 4
Communication port protocol	-
Communication port support	-
Data recording	Min/max of instantaneous values Time stamping 5 alarms
Mounting mode	Clip-on
Mounting support	DIN rail
Standards	EN 61010-1 IEC 61557-12 IEC 62052-11 EN 50470-1 EN 50470-3 EN 61557-12 UL 61010-1
Product certifications	CULus conforming to UL 61010-1 UL CE conforming to EN 61010-1
Width	90 mm
Depth	70 mm
Height	95 mm
Product weight	0.26 kg

Okolina

electromagnetic compatibility	<ul style="list-style-type: none"> • conducted and radiated emissions class class B, conforming to EN 55022 • electrostatic discharge class level 4, conforming to IEC 61000-4-2 • conducted RF disturbances class level 3, conforming to IEC 61000-4-6 • electrical fast transient/burst immunity test class level 4, conforming to IEC 61000-4-4 • susceptibility to electromagnetic fields class level 3, conforming to IEC 61000-4-3 • 1.2/50 μs shock waves immunity test class level 4, conforming to IEC 61000-4-5 • magnetic field at power frequency (0.5 mT), conforming to IEC 61000-4-8
overvoltage category	III
IP degree of protection	IP40 (front panel) conforming to IEC 60529 IP20 (body) conforming to IEC 60529
relative humidity	5...95 % 50 °C
pollution degree	2
ambient air temperature for operation	-25...55 °C
ambient air temperature for storage	-40...85 °C
operating altitude	0...3000 m

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1214 - Schneider Electric declaration of conformity	Compliant - since 1214 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------