



## Glavno

Range	Acti 9
Product name	Acti 9 D0
Product or component type	Fuse-switch disconnecter
Device short name	D02
Poles description	3P + N
Number of protected poles	3
Utilisation category	AC-22A conforming to IEC 60947-3

## Komplementarno

[In] rated current	63 A
Fuse curve	AM GG
Fuse size	15 x 36 mm
Fuse size code	D02
[Ue] rated operational voltage	230...400 V AC 50/60 Hz
[Ui] rated insulation voltage	400 V
[Uimp] rated impulse withstand voltage	6 kV
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	12
Height	88 mm
Width	108 mm
Depth	68 mm
Mechanical durability	8500 cycles open-close
Electrical durability	1500 cycles
Connections - terminals	Screw clamp terminals 1.5...35 mm <sup>2</sup> rigid Screw clamp terminals 1.5...25 mm <sup>2</sup> flexible Screw clamp terminals 1.5...25 mm <sup>2</sup> flexible with
Wire stripping length	14 mm
Tightening torque	3 N.m

## Okolina

standards	EN 60947-1 EN 60947-3 IEC 60269-1 IEC 60947-1 IEC 60947-3 IEC 60269-3
quality labels	VDE
IP degree of protection	IP20
ambient air temperature for operation	-5...40 °C
ambient air temperature for storage	-25...55 °C

## Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 0844 - Schneider Electric declaration of conformity	Compliant - since 0844 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.  
 Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.  
 Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje specifičnu primjenu ili uporabu istog.  
 Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

---

## Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---