

MGU3.107T.25

Unica – ozibna sklopka – 10 A, 250 V AC – 1 m – slonovača



Glavno

Range	Unica
Product or component type	Switch
Aesthetic name	Unica (standard aesthetic)
Device presentation	Mechanism
Switch function	2-way
Switch application	Roller blind
Rated current	10 A, 250 V AC, 50/60 Hz
Actuator	Rocker
Number of modules	1 module
Fixing mode	Clip-in
Cover plate colour tint	Ivory

Komplementarno

Contacts type and composition	1 C/O
Mechanical interlocking	Interlock between up/down
[Iu] rated interrupted current	Motor: 2.5 A
Opening distance	> 3 mm
Marking	Down UP
Connections - terminals	Screw terminals
Cable cross section	<= 2.5 mm ² (flexible) <= 2.5 mm ² (rigid)
Minimum load breaking capacity	200 operations 1.25 I _n and 1.1 U _n , cos phi: 0.3
Electrical durability	10000 cycles (cos phi: 0.6)
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	> 2000 V
Material	Mechanism cover: ASA + PC
Standards	EMC directive EN 60669-1 LV directive
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
Embedding depth	21 mm
Depth	33 mm
Width	22.4 mm
Height	45 mm

Okolina

IK degree of protection	IK01
IP degree of protection	IP20
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

UV resistant
Window-cleaning fluid

environmental health and issues

Halogen free

Offer Sustainability

Green Premium product

Green Premium product

Compliant - since 1834 - Schneider Electric declaration of conformity

Compliant - since 1834 - Schneider Electric declaration of conformity

Reference not containing SVHC above the threshold

Reference not containing SVHC above the threshold

Available

Available

Need no specific recycling operations

Need no specific recycling operations

Contractual warranty

Warranty period

18 months
