

## MGU3.108T.12

Unica Top/Class – ozibna sklopka – 10 A, 250 V AC  
– 1 m – grafit



### Glavno

Range	Unica
Device application	Control
Product or component type	Switch
Aesthetic name	Unica Top - Unica Class
Device presentation	Mechanism
Switch function	2-way
Switch application	Roller blind
Rated current	10 A, 250 V AC, 50/60 Hz
Actuator	Rocker
Number of modules	1 module
Fixing mode	Clip-in
Cover plate colour tint	Graphite

### Komplementarno

Contacts type and composition	1 C/O
Mechanical interlocking	Interlock between up/down
[Iu] rated interrupted current	Motor: 2.5 A
Opening distance	> 3 mm
Marking	Down UP
Connections - terminals	Screw terminals
Cable cross section	<= 2.5 mm <sup>2</sup> (flexible) <= 2.5 mm <sup>2</sup> (rigid)
Minimum load breaking capacity	200 operations 1.25 I <sub>n</sub> and 1.1 U <sub>n</sub> , cos phi: 0.3
Electrical durability	40000 cycles (cos phi: 0.6)
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	> 2000 V
Material	Mechanism cover: ASA + PC
Standards	EMC directive EN 60669-1 LV directive
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
Embedding depth	21 mm
Depth	33 mm

### Okolina

IK degree of protection	IK01
IP degree of protection	IP20
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid

Informacije dane u ovoj dokumentaciji sadrže opće i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

---

environmental health and issues	Halogen free
---------------------------------	--------------

---

### Offer Sustainability

---

Green Premium product	Green Premium product
Compliant - since 1834 - Schneider Electric declaration of conformity	Compliant - since 1834 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

---

### Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---