

Podatkovni list proizvoda**Karakteristike****MGU3.109T.18**

Unica – ozibna sklopka – 10 AX, 250 V AC – 1 m – bijela

**Glavno**

Range	Unica
Device application	Control
Product or component type	Switch
Aesthetic name	Unica (standard aesthetic)
Device presentation	Mechanism
Switch function	Double 2-way
Switch application	Roller blind
Rated current	10 AX, 250 V AC, 50/60 Hz
Actuator	Rocker
Number of modules	1 module
Fixing mode	Clip-in
Cover plate colour tint	White

Komplementarno

Contacts type and composition	1 C/O + 1 C/O
Mechanical interlocking	Interlock between up/down
[I _u] rated interrupted current	Motor: 2.5 A
Opening distance	> 3 mm
Marking	Down UP
Connections - terminals	Screw terminals
Cable cross section	<= 2.5 mm ² (flexible) <= 2.5 mm ² (rigid)
Minimum load breaking capacity	200 operations 1.25 In and 1.1 Un, cos phi: 0.3
Electrical durability	10000 cycles (cos phi: 0.6)
Insulation resistance	> 5 MΩ @ 500 V
Dielectric strength	> 2000 V
Material	Mechanism cover: ASA + PC
Standards	EMC directive EN 60669-1 LV directive
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
Embedding depth	21 mm
Depth	33 mm
Width	22.4 mm
Height	45 mm

Okolina

IK degree of protection	IK01
IP degree of protection	IP20
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil

Petrol	
UV resistant	
Window-cleaning fluid	
environmental health and issues	Halogen free

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1834 - Schneider Electric declaration of conformity	Compliant - since 1834 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------