

MGU3.161.30S

Unica Top/Class – ozibna sklopka – 1–smjerno – 16
AX 250 V AC – 1 m – alum.



Glavno

Range	Unica
Aesthetic name	Unica Top - Unica Class
Device application	Control
Product or component type	Switch
Device presentation	Mechanism
Switch function	1-pole 1-way
Colour tint	Aluminium

Komplementarno

Rated current	16 AX, 250 V AC, 50/60 Hz
Electrical durability	5000 cycles
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	2000 V
Minimum load breaking capacity	200 operations 1.25 In and 1.1 Un, cos phi: 0.3
Opening distance	> 3 mm
Actuator	Rocker
Number of modules	1 module
Pilot light	Amber LED: 0.15 mA (temperature : 15 °C)
Connections - terminals	Screw terminals
Cable cross section	0...4 mm ² (rigid) 0...4 mm ² (flexible)
Material	Mechanism cover: ABS (acrylonitrile butadiene-styrene)
Fixing mode	Clip-in
Width	22.5 mm
Height	45 mm
Depth	33 mm
Embedding depth	21 mm
Product weight	0.0239 kg
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
Standards	EMC directive EN 60669-1 LV directive

Okolina

IP degree of protection	IP20
IK degree of protection	IK01
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Offer Sustainability

Green Premium product

Green Premium product

Compliant - since 0622 - Schneider Electric declaration of conformity

Compliant - since 0622 - Schneider Electric declaration of conformity

Reference not containing SVHC above the threshold

Reference not containing SVHC above the threshold

Available

Available

Need no specific recycling operations

Need no specific recycling operations

Contractual warranty

Warranty period

18 months
