

## MGU3.206.25CN

Unica – tipkalo – 1–smjerno – 10 A 250 V AC – 2 m  
– slonovača



### Glavno

Range	Unica
Aesthetic name	Unica (standard aesthetic)
Device application	Bell switch
Product or component type	Switch
Device presentation	Mechanism
Switch function	1-pole 1-way
Colour tint	Ivory

### Komplementarno

Rated current	10 A, 250 V AC, 50/60 Hz
Electrical durability	40000 cycles (cos phi: 0.6)
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	2000 V
Minimum load breaking capacity	200 operations 1.25 In and 1.1 Un, cos phi: 0.3
Condition of use	Impulse relay control
Opening distance	> 3 mm
Actuator	Push-button
Number of modules	2 modules
Pilot light	Blue LED: 0.15 mA (temperature : 15 °C)
Connections - terminals	Screwless terminals
Cable cross section	0...2.5 mm <sup>2</sup> (rigid) 0...2.5 mm <sup>2</sup> (flexible)
Material	Mechanism cover: ASA + PC
Marking	Bell symbol
Fixing mode	Clip-in
Width	45 mm
Height	45 mm
Depth	34 mm
Embedding depth	22 mm
Product weight	0.0226 kg
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
Standards	EMC directive EN 60669-1 LV directive

### Okolina

IP degree of protection	IP20
IK degree of protection	IK01
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

	Petrol UV resistant Window-cleaning fluid
environmental health and issues	Halogen free

### Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0622 - Schneider Electric declaration of conformity	Compliant - since 0622 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------