

## MGU3.421.30

Unica Top/Class – 1 RJ45 utičnica (S-One) – 2 m –  
Kat.5e, UTP – alum.



### Glavno

Range	Unica
Aesthetic name	Unica Top - Unica Class
Product or component type	RJ45 connector
Device presentation	Mechanism
Colour tint	Aluminium
Data socket type	RJ45 - 8 contacts - category 5e - transmission rate < 155 MHz
Provided equipment	Label holder Protective flap

### Komplementarno

Communication network type	1000BASE-T
Communication port protocol	ATM 155 Mbps
Number of modules	2 modules
Socket number	1
Type of footprint	Infraplus
Connector type	S-One
Cable shielding type	U/UTP
Organization of wire	Unshielded twisted pair
Connections - terminals	Click
Fixing mode	Clip-in
Material	Mechanism cover: ABS (acrylonitrile butadiene-styrene)
Depth	36 mm
Width	85 mm
Height	80 mm
Embedding depth	25 mm
Product weight	0.016 kg
Market segment	Residential Small commercial

### Okolina

IP degree of protection	IP40
IK degree of protection	IK01
ambient air temperature for operation	15...30 °C
ambient air temperature for storage	0...35 °C
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
environmental health and issues	Halogen free
standards	ISO 8877

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

## Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0702 - Schneider Electric declaration of conformity	Compliant - since 0702 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------