



### Glavno

Range	Unica
Product or component type	USB charger
Device presentation	Mechanism

### Komplementarno

Device application	Charger
Device mounting	Flush
Colour tint	White
Connector type	USB 2.0
[Ue] rated operational voltage	100...240 V AC 50/60 Hz
Power consumption in W	<= 0.1 W
Input power	7.5 W
Socket number	1
Integrated connection type	1 USB 2.0 port 5 V DC, maximum load current: 1 A
Material	Casing: PC (polycarbonate) GF10 FR Internal cover: PC (polycarbonate) GF10 FR Centre plate : ABS (acrylonitrile butadiene-styrene)
Protection type	Short-circuit protection
Number of terminals	2 screw terminals
Shape of screw head	Pozidriv No 1
Clamping connection capacity	1.5...2.5 mm <sup>2</sup> rigid 1.5...2.5 mm <sup>2</sup> flexible 1.5...2.5 mm <sup>2</sup> stranded
Wire stripping length	8 mm
Product compatibility	All devices fulfilling the EN 62684 standard
Fixing mode	Screws or claws
Type of packing	Flow-pack
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-5...50 °C
Standards	2004/108/EC EN 60950-1 2006/95/EC EN 62684 EU directive 2002/95/EC WEEE directive 2002/96/EC ETSI EN 301 489-4
Height	45 mm
Width	22.5 mm
Depth	42 mm
Embedding depth	30.8 mm
Product weight	0.03 kg

### Okolina

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.  
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.  
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.  
Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

electrical insulation class	Class II
environmental characteristic	REACH Regulation (EC) No 1907/2006
IK degree of protection	IK04
IP degree of protection	IP20

### Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1834 - Schneider Electric declaration of conformity	Compliant - since 1834 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations