

MGU3.455.18

Unica – Utičnica za R-TV/SAT – priključna utičnica – bijela



Glavno

Range	Unica
Aesthetic name	Unica (standard aesthetic)
Product or component type	R-TV/SAT socket
Device presentation	Mechanism
TV socket type	End-of-line (terminal socket)
Colour tint	White

Komplementarno

TV connector	Male IEC 9.52 mm
SAT connector	Female IEC 9.52 mm
Path attenuation	R: < 9 dB @10...108 MHz TV/UHF: < 9 dB @470...830 MHz TV/VHF: < 9 dB @118...470 MHz SAT: < 17 dB @950...2400 MHz
DC current flow	In SAT socket
Number per line	1
Number of modules	2 modules
Material	Mechanism cover: ASA + PC
Condition of use	Series distribution systems
Fixing mode	Clip-in
Depth	28 mm
Width	45 mm
Height	45 mm
Embedding depth	18 mm
Product weight	0.073 kg

Okolina

IP degree of protection	IP20
IK degree of protection	IK01
ambient air temperature for operation	15...35 °C
ambient air temperature for storage	0...35 °C
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
environmental health and issues	Halogen free
standards	DIN 45325 DIN 45330 EMC directive EN 50083-1 EN 50083-2

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0702 - Schneider Electric declaration of conformity	Compliant - since 0702 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------
