

## MGU3.524.18

Unica – detektor pokreta 300 W – 230 V AC – 2 m – bijela



### Glavno

Range	Unica
Aesthetic name	Unica (standard aesthetic)
Product or component type	Movement detector
Device presentation	Mechanism
Load type	230 V AC halogen lamp - 300 W 230 V AC incandescent lamp - 300 W 230 V AC convector - 300 W, cos phi: 0.95
Cover plate colour tint	White

### Komplementarno

Power range	300 W
[Ue] rated operational voltage	230 V AC (+/- 10 %), 50/60 Hz
Movement detection area	10 x 20 m (PIR mounting height 2.15 m) 9 x 18 m (PIR mounting height 1.2 m)
Presence detection area	5 x 10 m (PIR mounting height 1.2 m) 6 x 12 m (PIR mounting height 2.15 m)
Detection angle	Full 180° Partial 90° left or right
Selection modes	A: automatic M: manual
Number of pin in parallel	2 (50...300 W) 3 (80...300 W) 4 (100...300 W) 5 (140...300 W)
Number of modules	2 modules
Type of setting	Adjustable disconnection time and brightness
Control type	Manual override with 5 push-buttons maximum
Wiring configuration	2 wires
Light intensity adjustment	5...1000 lux
Time delay range	2 s...20 min
Clamping connection capacity	<= 2 x 2.5 mm <sup>2</sup> for flexible cable(s) <= 2 x 2.5 mm <sup>2</sup> for rigid cable(s)
Marking	L+N
Connections - terminals	Screw terminals
Material	Mechanism cover: ASA + PC
Fixing mode	Clip-in
Mounting height	> 1.2...< 2.15 m
Depth	58 mm
Width	45 mm
Height	45 mm
Embedding depth	34 mm
Product weight	0.058 kg

### Okolina

IP degree of protection	IP20
IK degree of protection	IK01

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i popunnu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

ambient air temperature for operation	-5...35 °C
ambient air temperature for storage	-20...55 °C
relative humidity	0...5 %
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
environmental health and issues	Halogen free
standards	EN 60669-2-1

### Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1426 - Schneider Electric declaration of conformity	Compliant - since 1426 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available

### Contractual warranty

Warranty period	18 months
-----------------	-----------