


## MGU3.525.18

Unica – detektor pokreta 2300 W – 230 V AC – 2 m  
– bijela



### Glavno

|                           |   |
|---------------------------|---|
| Range                     | Unica   |
| Aesthetic name            | Unica (standard aesthetic)  |
| Product or component type | Movement detector   |
| Device presentation       | Mechanism   |
| Load type                 | 230 V AC incandescent lamp - 2300 W<br>230 V AC halogen lamp - 2000 W<br>Low voltage halogen lamp with wire-wound transformer - 1500 VA<br>Low voltage lamps with electronic transformer - 1150 VA<br>230 V AC fan - 200 VA<br>230 V AC convector - 2300 W<br>230 V AC contactor - 200 VA<br>Compact fluorescent lamp - 500 VA<br>Fluorescent tube (diameter: 26...38 mm): 1 1-10 V dimmable electronic ballast - 2000 VA, cos phi: 0.9 |
| Cover plate colour tint   | White   |

### Komplementarno

|                                |   |
|--------------------------------|---|
| Power range                    | 2300 W  |
| [Ue] rated operational voltage | 230 V AC (+/- 10 %), 50/60 Hz   |
| Movement detection area        | 10 x 20 m (PIR mounting height 2.15 m)<br>9 x 18 m (PIR mounting height 1.2 m)                    |
| Presence detection area        | 5 x 10 m (PIR mounting height 1.2 m)<br>6 x 12 m (PIR mounting height 2.15 m)                     |
| Detection angle                | Full 180°<br>Partial 90° left or right  |
| Selection modes                | A: automatic<br>M: manual<br>S: slave   |
| Number of modules              | 2 modules   |
| Type of setting                | Adjustable disconnection time and brightness  |
| Control type                   | Manual override with 5 push-buttons maximum   |
| Wiring configuration           | 3 wires with neutral  |
| Light intensity adjustment     | 5...1000 lux  |
| Time delay range               | 2 s...20 min  |
| Clamping connection capacity   | <= 2 x 2.5 mm <sup>2</sup> for flexible cable(s)<br><= 2 x 2.5 mm <sup>2</sup> for rigid cable(s) |
| Marking                        | L+N   |
| Connections - terminals        | Screw terminals   |
| Material                       | Mechanism cover: ASA + PC   |
| Fixing mode                    | Clip-in   |
| Mounting height                | > 1.2...< 2.15 m  |
| Depth                          | 58 mm   |
| Width                          | 45 mm   |
| Height                         | 45 mm   |
| Embedding depth                | 34 mm   |
| Product weight                 | 0.076 kg  |

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.  
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.  
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje specifičnu primjenu ili uporabu istog.  
Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

## Okolina

|                                       |  |
|---------------------------------------|--|
| IP degree of protection               | IP20   |
| IK degree of protection               | IK01   |
| ambient air temperature for operation | -5...35 °C   |
| ambient air temperature for storage   | -20...55 °C  |
| relative humidity                     | 0...5 %  |
| environmental characteristic          | Acetone<br>Alcohol<br>Ammonia<br>Bleach<br>Liquid soap<br>Oil<br>Petrol<br>UV resistant<br>Window-cleaning fluid |
| environmental health and issues       | Halogen free   |
| standards                             | EN 60669-2-1   |

## Offer Sustainability

|   |   |
|---|---|
| Green Premium product   | Green Premium product   |
| Compliant - since 1426 - Schneider Electric declaration of conformity | Compliant - since 1426 - Schneider Electric declaration of conformity |
| Reference not containing SVHC above the threshold                     | Reference not containing SVHC above the threshold                     |
| Available   | Available   |
| Available   | Available   |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|