

## MGU3.530.25

Unica KNX – tipkalo – 2-smjerna – 10 A 24 V DC – 2 m – slonovača



### Glavno

Range	Unica
Aesthetic name	Unica KNX
Device application	Control
Product or component type	Switch
Device presentation	Mechanism
Bus type	KNX
Switch function	1-pole 2-way
Colour tint	Ivory

### Komplementarno

Rated current	10 A, 24 V DC
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	2000 V
Actuator	Push-button
Number of modules	2 modules
Pilot light	Blue LED: 1 mA (temperature : 15 °C)
Connections - terminals	Screwless terminals
Cable cross section	0...2.5 mm <sup>2</sup> (rigid) 0...2.5 mm <sup>2</sup> (flexible)
Material	Plastic
Device mounting	Flush
Fixing mode	Clip-in
Depth	38 mm
Embedding depth	13 mm
Ambient air temperature for operation	-5...45 °C
Standards	EMC directive EN 60669-1 LV directive

### Okolina

IP degree of protection	IP20
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
environmental health and issues	Halogen free

### Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1426 - Schneider Electric declaration of conformity	Compliant - since 1426 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold

Need no specific recycling operations

Need no specific recycling operations

---

**Contractual warranty**

Warranty period

18 months

---