



## Glavno

Range	Unica
Aesthetic name	Unica KNX
Device application	Control
Product or component type	Switch
Device presentation	Mechanism
Bus type	KNX
Switch function	1-pole 2-way
Number of rocker	2
Colour tint	Aluminium

## Komplementarno

Rated current	10 A, 24 V DC
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	2000 V
Actuator	Push-button
Number of modules	2 modules
Pilot light	Blue LED: 1 mA (temperature : 15 °C)
Connections - terminals	Screwless terminals
Cable cross section	0...2.5 mm <sup>2</sup> (rigid) 0...2.5 mm <sup>2</sup> (flexible)
Material	Plastic
Surface finish	Varnished
Device mounting	Flush
Fixing mode	Clip-in
Depth	38 mm
Embedding depth	13 mm
Ambient air temperature for operation	-5...45 °C
Standards	EMC directive EN 60669-1 LV directive

## Okolina

IP degree of protection	IP20
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
environmental health and issues	Halogen free

## Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1426 - Schneider Electric declaration	Compliant - since 1426 - Schneider Electric declaration of conformity

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.  
 Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.  
 Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.  
 Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

of conformity

---

Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Need no specific recycling operations	Need no specific recycling operations

---

**Contractual warranty**

---

Warranty period	18 months
-----------------	-----------

---