

Podatkovni list proizvoda**Karakteristike****MGU3.532.18**

Unica KNX – infracrveno tipkalo – 2-smjerna – 10 A,
250 V AC – 2 m – bijela

**Glavno**

Range	Unica
Aesthetic name	Unica KNX
Product or component type	Switch
Device application	Control
Device presentation	Mechanism
Bus type	KNX
Sensor type	Infrared sensor
Cover plate colour tint	White (RAL 1013)

Komplementarno

Rated current	10 A, 250 V AC, 50/60 Hz
Insulation resistance	> 5 MΩ @ 500 V
Dielectric strength	> 2000 V
Number of modules	2 modules
Switch function	2-way
Contacts type and composition	2 NO
Opening distance	> 3 mm
Transmission support medium	Infrared
Actuator	Push-button
Pilot light	Blue LED: 1 mA (temperature : 15 °C)
Connections - terminals	Screwless terminals
Cable cross section	<= 2.5 mm² (flexible) <= 2.5 mm² (rigid)
Material	Plastic
Surface finish	Brilliant
Device mounting	Flush
Fixing mode	Screws

Okolina

IP degree of protection	IP20
IK degree of protection	IK01
ambient air temperature for operation	-5...45 °C
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
environmental health and issues	Halogen free
standards	EMC directive LV directive

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1426 - Schneider Electric declaration of conformity	Compliant - since 1426 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------