


MGU3.532.30

Unica KNX – infracrveno tipkalo – 2-smjerna – 10 A,
250 V AC – 2 m – aluminij



Glavno

Range	Unica
Aesthetic name	Unica KNX
Product or component type	Switch
Device application	Control
Device presentation	Mechanism
Cover plate colour tint	Aluminium

Komplementarno

Rated current	10 A, 250 V AC, 50/60 Hz
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	> 2000 V
Number of modules	2 modules
Switch function	2-way
Contacts type and composition	2 NO
Opening distance	> 3 mm
Transmission support medium	Infrared
Actuator	Push-button
Pilot light	Blue LED: 1 mA (temperature : 15 °C)
Connections - terminals	Screwless terminals
Cable cross section	<= 2.5 mm ² (flexible) <= 2.5 mm ² (rigid)
Fixing mode	Screws

Okolina

IP degree of protection	IP20
IK degree of protection	IK01
ambient air temperature for operation	-5...45 °C
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
environmental health and issues	Halogen free
standards	EMC directive LV directive

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1426 - Schneider Electric declaration of conformity	Compliant - since 1426 - Schneider Electric declaration of conformity

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Reference not containing SVHC above the threshold

Reference not containing SVHC above the threshold

Need no specific recycling operations

Need no specific recycling operations

Contractual warranty

Warranty period

18 months
