

## MGU3.533.25

Unica KNX – detektor pokreta – 230 V AC – 2 m – slonovača



### Glavno

Range	Unica
Aesthetic name	Unica KNX
Product or component type	Movement detector
Device application	Lighting
Device presentation	Mechanism
Product specific application	Staircase monitoring
Bus type	KNX
Cover plate colour tint	Ivory (RAL 9010)

### Komplementarno

[Ue] rated operational voltage	230 V AC (+/- 10 %), 50/60 Hz
Movement detection area	9 x 9 m(PIR mounting height 2.15m)
Detection face	Lateral: 9 m
Horizontal detection angle	0...180 °
Number of modules	2 modules
Type of setting	Light sensitivity adjustable
Light intensity adjustment	10...< 1000 lux @rotary switch 10...2000 lux @ETS
Time delay range	1 s...8 minfor rotary switch 1 s...255 hfor ETS
Duty cycle	15300 minutes
Clamping connection capacity	<= 2 x 2.5 mm <sup>2</sup> for flexible cable(s) <= 2 x 2.5 mm <sup>2</sup> for rigid cable(s)
Connections - terminals	Screwless terminals
Material	Mechanism cover: ASA + PC Fixing frame: zamak
Surface finish	Brilliant
Device mounting	Flush
Fixing mode	Clip-in
Mounting height	1...2.15 m
Depth	56 mm
Embedding depth	34 mm

### Okolina

IP degree of protection	IP20
ambient air temperature for operation	-5...45 °C
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
environmental health and issues	Halogen free
standards	EMC directive

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poplunu analizu rizika, procjenu i ispitivanje specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

**Offer Sustainability**

Green Premium product	Green Premium product
Compliant - since 1342 - Schneider Electric declaration of conformity	Compliant - since 1342 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available

**Contractual warranty**

Warranty period	18 months
-----------------	-----------