

MGU3.533.30

Unica KNX – detektor pokreta – 230 V AC – 2 m –
aluminij



Glavno

Range	Unica
Aesthetic name	Unica KNX
Product or component type	Movement detector
Device presentation	Mechanism
Cover plate colour tint	Aluminium

Komplementarno

[Ue] rated operational voltage	230 V AC (+/- 10 %), 50/60 Hz
Movement detection area	9 x 9 m(PIR mounting height 2.15m)
Detection angle	Full 180°
Number of modules	2 modules
Light intensity adjustment	10...< 1000 lux @rotary switch 10...2000 lux @ETS
Time delay range	1 s...8 minfor rotary switch 1 s...255 hfor ETS
Clamping connection capacity	<= 2 x 2.5 mm ² for flexible cable(s) <= 2 x 2.5 mm ² for rigid cable(s)
Connections - terminals	Screwless terminals
Material	Mechanism cover: ASA + PC Fixing frame: zamak
Fixing mode	Clip-in
Mounting height	1...2.5 m
Depth	56 mm
Embedding depth	34 mm

Okolina

IP degree of protection	IP20
ambient air temperature for operation	-5...45 °C
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
environmental health and issues	Halogen free
standards	EMC directive LV directive

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1342 - Schneider Electric declaration	Compliant - since 1342 - Schneider Electric declaration of conformity

of conformity

Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------