

## MGU3.534.12

Unica KNX – jedinica za regulaciju sobne temperature  
– 230 V AC – 2 m – grafit



### Glavno

Range	Unica
Aesthetic name	Unica KNX
Product or component type	Room temperature control unit
Device application	Control
Device presentation	Mechanism
Colour tint	Graphite
Bus type	KNX

### Komplementarno

[Ue] rated operational voltage	230 V AC (+/- 10 %), 50/60 Hz
Type of setting	Manual set point adjustment
Number of modules	2 modules
Device composition	Display 4 buttons
Control type	Local control
Clamping connection capacity	<= 2 x 2.5 mm <sup>2</sup> for flexible cable(s) <= 2 x 2.5 mm <sup>2</sup> for rigid cable(s)
Contacts type and composition	1 C/O
Connections - terminals	Screwless terminals
Information displayed	Day Time Operating mode Temperature
Status LED	Programming LED
Programmable temperature	No
Temperature setting range	0...40 °C
Measurement accuracy	± 1 K
Material	Plastic
Surface treatment	Varnished
Surface finish	Brilliant
Device mounting	Flush
Fixing mode	Clip-in
Mounting height	> 1.5 m
Depth	39 mm
Embedding depth	26 mm

### Okolina

IP degree of protection	IP20
IK degree of protection	IK01
ambient air temperature for operation	-5...45 °C
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.  
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.  
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.  
Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

	Window-cleaning fluid
environmental health and issues	Halogen free
standards	EMC directive LV directive

### Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 1426 - Schneider Electric declaration of conformity	Compliant - since 1426 - Schneider Electric declaration of conformity
Need no specific recycling operations	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------