

MGU3.540.18

Unica-sklopka za ključ-kartice s vremenskom
odgodom-8 A-230 V AC-2 m-bijela



Glavno

Range	Unica
Aesthetic name	Unica (standard aesthetic)
Product or component type	Time delayed key card switch
Device application	Control
Device presentation	Mechanism
Cover plate colour tint	White

Komplementarno

[Ue] rated operational voltage	230 V +/- 10 % AC 50 Hz
Rated current	8 A
Load type	230 V AC incandescent lamp - 1470 W 230 V AC halogen lamp - 1470 W 230 V AC fan - 1470 W 230 V AC convector - 1470 W Low voltage halogen lamp with ferromagnetic transformer - 1000 VA Low voltage halogen lamp with electronic transformer - 1470 VA Fluorescent tube ferromagnetic ballast - 1470 VA Compact fluorescent lamp - 1470 W LED lamp - 1470 W Contactor
Actuator	Card 54 x 86 x 0.85 mm (maximum)
Number of modules	2 modules
Fuse type	Electronic
Maximum number of switchings	50000 operations
Protection type	Overvoltage protection Thermal protection
Pilot light	Amber indicator lamp
Time delay	Adjustable between 10 s and 3 mn
Marking	Vertical insertion pictogram
Connections - terminals	Screw terminals
Clamping connection capacity	<= 2 x 2.5 mm ² for flexible cable(s) <= 2 x 2.5 mm ² for rigid cable(s)
Fixing mode	Clip-in
Material	Mechanism cover: ASA + PC
Embedding depth	14 mm
Depth	Unica Basic cover frame: 36 mm Unica Colors cover frame: 36 mm Unica Allegro cover frame: 35 mm Unica Plus cover frame: 35 mm
Width	45 mm
Height	45 mm
Product weight	0.045 kg

Okolina

IP degree of protection	IP20
IK degree of protection	IK01

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

ambient air temperature for operation	5...30 °C
ambient air temperature for storage	-20...60 °C
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
environmental health and issues	Halogen free
standards	EN 60669-1

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1426 - Schneider Electric declaration of conformity	Compliant - since 1426 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------