

MGU3.862.18

Unica – kabelaška utičnica – 16 A – 2 m – bijela



Glavno

Range	Unica
Accessory / separate part category	Cabling accessory
Product or component type	Cable outlet
Aesthetic name	Unica (standard aesthetic)
Device presentation	Mechanism
Number of modules	2 modules
Fixing mode	Clip-in
Provided equipment	Anti-tug clamps
Colour tint	White (RAL 9003)

Komplementarno

Range compatibility	Unica
Rated current	16 A
Connections - terminals	Screw terminals
Clamping connection capacity	<= 3 x 2.5 mm ² for flexible cable(s) <= 3 x 2.5 mm ² for rigid cable(s)
Material	Mechanism cover: ASA + PC
Product certifications	CE ES.ME01.B02319 AC EAC
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Width	45 mm
Height	45 mm
Product weight	0.0178 kg

Okolina

IK degree of protection	IK01
IP degree of protection	IP40
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
environmental health and issues	Halogen free

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1834 - Schneider Electric declaration of conformity	Compliant - since 1834 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Contractual warranty

Warranty period

18 months