



## Glavno

|                           |  |
|---------------------------|--|
| Range                     | Unica                                  |
| Device application        | Mounting                               |
| Product or component type | Cover frame                            |
| Aesthetic name            | Unica Quadro                           |
| Number of gangs           | 2 gangs horizontal<br>2 gangs vertical |
| Fixing mode               | Clip-in                                |
| Cover frame colour tint   | Salmon                                 |

## Komplementarno

|                          |   |
|--------------------------|---|
| Material                 | ABS (acrylonitrile butadiene-styrene) cover frame |
| Standards                | EN 60669-1  |
| Height                   | 87 mm   |
| Width                    | 158 mm  |
| Depth                    | 14 mm   |
| Distance between centers | 71 mm   |
| Product weight           | 0.028 kg  |
| Market segment           | Residential<br>Small commercial                   |

## Okolina

|                                 |  |
|---------------------------------|--|
| IK degree of protection         | IK01   |
| IP degree of protection         | IP20   |
| environmental characteristic    | Acetone<br>Alcohol<br>Ammonia<br>Bleach<br>Liquid soap<br>Oil<br>Petrol<br>UV resistant<br>Window-cleaning fluid |
| environmental health and issues | Halogen free   |

## Offer Sustainability

|   |   |
|---|---|
| Green Premium product   | Green Premium product   |
| Compliant - since 1834 - Schneider Electric declaration of conformity | Compliant - since 1834 - Schneider Electric declaration of conformity |
| Reference not containing SVHC above the threshold                     | Reference not containing SVHC above the threshold                     |
| Available   | Available   |
| Need no specific recycling operations                                 | Need no specific recycling operations                                 |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i poipunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.