

MGU5.513.18

UNICA univerzalni rotacijski regulator rasvjete za LED lampe 400 W, bijeli



Main

Range	Unica
Range of product	Unica
Device short name	SBD200LED
Product or component type	Dimmer
Device application	Control

Complementary

Dimmer type	Universal
Dimmer control	Rotary push type
Control type	Rotary push type
Switch function	1-pole 2-way
Load type	Incandescent lamp 230 V halogen lamp LED lamp Low voltage halogen lamp with ferromagnetic transformer Low voltage halogen lamp with electronic transformer
Power range	Halogen lamp 4...400 W Incandescent lamp 4...400 W LED lamp 4...40 W RL LED mode) LED lamp 4 W...200 VA RC LED mode) Low voltage halogen lamp with electronic transformer 4...400 W Low voltage halogen lamp with ferromagnetic transformer 4 W...400 VA
[Ue] rated operational voltage	230 V AC 50/60 Hz
Rated current/voltage	10 A 230 V AC
Protection type	Electronic short-circuit and automatic overload protection
Connections - terminals	Screw terminals
Number of loop terminals	1
Clamping connection capacity	1 x 2.5 mm ² solid or flexible with sleeve 2 x 1.5 mm ² solid or flexible with sleeve
Colour	White
Material	Thermoplastic central plate Thermoplastic knob
Device mounting	Flush
Fixing mode	By screws
Number of modules	2 modules
Embedding depth	34 mm
Maksimalna visina	71 mm
Maksimalna širina	71 mm
Maksimalna dubina	54 mm

Environment

Ambient air temperature for operation	-5...35 °C
Relative humidity	5...95 %
IP degree of protection	IP20 also with visual parts removed

Offer Sustainability

Direktiva EU RoHS	Sukladno Izjava EU RoHS
Bez žive	Da
Informacije o RoHS izuzeću	Da
Propis RoHS za Kinu	Izjava RoHS Za Kinu
WEEE	Proizvod se na tržištima EU mora odlagati u skladu sa specifičnim propisima o prikupljanju otpada; nikako se ne smije odlagati s komunalnim otpadom.