

## MGU5.513.30

UNICA univerzalni rotacijski regulator rasvjete za LED lampe 400 W, aluminij



### Main

Range	Unica
Range of product	Unica
Device short name	SBD200LED
Product or component type	Dimmer
Device application	Control

### Complementary

Dimmer type	Universal
Dimmer control	Rotary push type
Control type	Rotary push type
Switch function	1-pole 2-way
Load type	Incandescent lamp 230 V halogen lamp LED lamp Low voltage halogen lamp with ferromagnetic transformer Low voltage halogen lamp with electronic transformer
Power range	Halogen lamp 4...400 W Incandescent lamp 4...400 W LED lamp 4...40 W RL LED mode) LED lamp 4 W...200 VA RC LED mode) Low voltage halogen lamp with electronic transformer 4...400 W Low voltage halogen lamp with ferromagnetic transformer 4 W...400 VA
[Ue] rated operational voltage	230 V AC 50/60 Hz
Rated current/voltage	10 A 230 V AC
Protection type	Electronic short-circuit and automatic overload protection
Connections - terminals	Screw terminals
Number of loop terminals	1
Clamping connection capacity	1 x 2.5 mm <sup>2</sup> solid or flexible with sleeve 2 x 1.5 mm <sup>2</sup> solid or flexible with sleeve
Colour	Aluminium
Material	Thermoplastic central plate Thermoplastic knob
Device mounting	Flush
Fixing mode	By screws
Number of modules	2 modules
Embedding depth	34 mm
Maksimalna visina	71 mm
Maksimalna širina	71 mm
Maksimalna dubina	54 mm

## Environment

Ambient air temperature for operation	-5...35 °C
Relative humidity	5...95 %
IP degree of protection	IP20 also with visual parts removed

## Offer Sustainability

Direktiva EU RoHS	Sukladno <a href="#">Izjava EU RoHS</a>
Bez žive	Da
Informacije o RoHS izuzeću	<a href="#">Da</a>
Propis RoHS za Kinu	<a href="#">Izjava RoHS Za Kinu</a>
WEEE	Proizvod se na tržištima EU mora odlagati u skladu sa specifičnim propisima o prikupljanju otpada; nikako se ne smije odlagati s komunalnim otpadom.