



Glavno

Range	Unica
Device application	Mounting
Product or component type	Cover frame
Aesthetic name	Unica Plus
Number of modules	6 modules
Fixing mode	Clip-in
Cover frame colour tint	Sand
Decoration colour	White

Komplementarno

Material	ABS (acrylonitrile butadiene-styrene) cover frame ASA + PC decorative frame ASA + PC intermediate part
Standards	EN 60669-1
Height	12 mm
Width	200 mm
Depth	84 mm
Product weight	0.036 kg
Market segment	Residential Small commercial

Okolina

IK degree of protection	IK01
IP degree of protection	IP20
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
environmental health and issues	Halogen free

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1834 - Schneider Electric declaration of conformity	Compliant - since 1834 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.
Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.