

## MGU8.002.18

Unica Basic/Colors–površinska kutija–bijela 2 m–4 perforirana otvora–bijela



### Glavno

Range	Unica
Device application	Mounting
Product or component type	Mounting box for mechanism
Aesthetic name	Unica Basic Unica Colors
Number of modules	2 modules
Number of gangs	1 gang
Fixing mode	By 4 pins
Additional information	Flame resistance 650 °C-30 s Self-extinguishing materials
Box colour tint	White

### Komplementarno

Wiring device mounting	Surface
Cable entry	4 knock-outs
Product compatibility	For universal fixing frame
Material	ASA + PC for box
Depth	36 mm
Width	85 mm
Height	80 mm
Product weight	0.0541 kg

### Okolina

standards	RoHS compliant UNE 60670-1
IK degree of protection	IK01
IP degree of protection	IP20
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid

### Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1834 - Schneider Electric declaration of conformity	Compliant - since 1834 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

### Contractual warranty

Warranty period	18 months
-----------------	-----------