


## MGU87.026.18

Unica Plus – površinska kutija s okvirom za fiksiranje  
– 6 m – 6 otvora – bijela



### Glavno

Range	Unica
Device application	Mounting
Product or component type	Mounting box
Aesthetic name	Unica (standard aesthetic)
Device presentation	Assembly
Number of modules	6 modules
Number of gangs	3 gangs
Fixing mode	Pins
Colour tint	White

### Komplementarno

Provided equipment	Fixing frame
Device mounting	Surface
Cable entry	6 knock-outs
Fire resistance	650 °C @30 s
Material	Box: ASA + PC Fixing frame: PBT (polybutylene terephthalate)
Standards	UNE 60670-1
Depth	28 mm
Width	231 mm
Height	79 mm
Product weight	0.139 kg

### Okolina

IK degree of protection	IK01
IP degree of protection	IP20
environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
environmental health and issues	Halogen free

### Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1834 - Schneider Electric declaration of conformity	Compliant - since 1834 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.