

MIP12312

mini Pragma površinsko kućište – 3 x 12 modula –
obična vrata



Glavno

Range	Mini Pragma
Product or component type	Enclosure
Enclosure type	Modular enclosure
Number of 18 mm modules per row	12
Number of horizontal rows	3
Type of front cover	Plain
Width	268 mm outside
Height	478 mm outside
Depth	102 mm outside

Komplementarno

Enclosure mounting	Surface
9 mm pitches	24
Total number of 18 mm modules	36
[In] rated current	63 A
Type of rail	35 mm asymmetrical rail
Cable entry	1 bare flange 1 trunking flange
Terminal block function	Earth / neutral
Number of terminal blocks	1 earth terminal block with 20 screwed outgoers 1 neutral terminal block with 20 screwed outgoers
Distribution block outgoers	2 x 16 mm ² for earth 2 x 16 mm ² for neutral 9 x 10 mm ² for earth 9 x 10 mm ² for neutral 9 x 6 mm ² for earth 9 x 6 mm ² for neutral
Enclosure material	Back part: technoplastic Door: technoplastic Front face: technoplastic
Colour	Door: white (RAL 9003) Front face: white (RAL 9003)

Okolina

standards	EN 50102 IEC 529 IEC 60439-3 IEC 60670-24 IEC 60695-2-11
quality labels	IMQ
fire resistance	Door: 650 °C Front face: 650 °C Back part: 650 °C
IP degree of protection	IP40
IK degree of protection	IK07
ambient air temperature for operation	-25...60 °C

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0901 - Schneider Electric declaration of conformity	Compliant - since 0901 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------