



Glavno

Range	Mini Pragma
Product or component type	Enclosure
Enclosure type	Modular enclosure
Number of 18 mm modules per row	4
Number of horizontal rows	1
Type of front cover	Smoked
Width	126 mm wall 150 mm outside
Height	228 mm wall 252 mm outside
Depth	18 mm outside 80 mm wall 98 mm total
Embedding depth	80 mm

Komplementarno

Enclosure mounting	Flush
9 mm pitches	8
Total number of 18 mm modules	4
[In] rated current	50 A
Type of rail	35 mm asymmetrical rail
Cable entry	Pre-cutted holes
Terminal block function	Earth / neutral
Number of terminal blocks	1 earth terminal block with 4 screwed outgoers 1 neutral terminal block with 4 screwed outgoers
Distribution block outgoers	1 x 16 mm ² for earth 1 x 16 mm ² for neutral 1 x 6 mm ² for earth 1 x 6 mm ² for neutral 2 x 10 mm ² for earth 2 x 10 mm ² for neutral
Enclosure material	Back part: technoplastic Door: technoplastic Front face: technoplastic
Colour	Front face: white (RAL 9003) Door : smoked (RAL 9003)

Okolina

standards	EN 50102 IEC 529 IEC 60439-3 IEC 60670-24 IEC 60695-2-11
quality labels	IMQ
fire resistance	Door: 650 °C Front face: 650 °C Back part: 650 °C
IP degree of protection	IP40
IK degree of protection	IK07
ambient air temperature for operation	-25...60 °C

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda.
Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene.
Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog.
Niti društvo Schneider Electric, Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0901 - Schneider Electric declaration of conformity	Compliant - since 0901 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------