

OVA37067E

Rilux-blok svjetla u slučaju nužde-standardan-
pripravan spoj-1 sat-90 lm



Glavno

Range	Rilux
Product or component type	Emergency light fitting
Device application	Lighting
Function	Standard
Supply	Non-maintained
Colour	White
Light source	Fluorescent tube x 8 W G5
Light source colour	White
Cover type	Transparent
Number of batteries	1 x 2.4 V 1.5 AH Ni-Cd (Nickel-Cadmium)
Wiring device additional information	Can be inhibited with rest mode via Teleur range of remote controls

Komplementarno

[Ue] rated operational voltage	200...230 V AC/DC at 50 Hz
Power consumption in VA	2.5 VA
Current consumption	10 mA
Electrical insulation class	Class II
Autonomy	1 h
Charging time	24 h
Luminous flux	Emergency condition: 90 lm
Material	Housing: plastic Cover: plastic
Device mounting	Flush Surface ceiling Surface wall
Height	100 mm
Width	331 mm
Depth	46 mm
Product weight	0.63 kg
Market segment	Small commercial

Okolina

IP degree of protection	IP40
IK degree of protection	IK06
ambient air temperature for operation	0...40 °C
fire resistance	850 °C
standards	EN 60598-2-22 IEC 50-11 IEC 695-2-1 EN 60695-2-10

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0833 - Schneider Electric declaration of conformity	Compliant - since 0833 - Schneider Electric declaration of conformity

Informacije dane u ovoj dokumentaciji sadrže opće opisne i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Reference contains SVHC above the threshold - go to CaP for more details

Reference contains SVHC above the threshold

Available

Available

Available

Available

Contractual warranty

Warranty period

18 months
