

OVA37068E

Rilux-blok svjetla u slučaju nužde-standardan-
pripravan spoj-3 sata-90 lm



Glavno

| | |
|--------------------------------------|---|
| Range | Rilux |
| Product or component type | Emergency light fitting |
| Device application | Lighting |
| Function | Standard |
| Supply | Non-maintained |
| Colour | White |
| Light source | Fluorescent tube x 8 W G5 |
| Light source colour | White |
| Cover type | Transparent |
| Number of batteries | 1 x 6 V 1.5 AH Ni-Cd (Nickel-Cadmium) |
| Wiring device additional information | Can be inhibited with rest mode via Teleur range of remote controls |

Komplementarno

| | |
|--------------------------------|--|
| [Ue] rated operational voltage | 200...230 V AC/DC at 50 Hz |
| Power consumption in VA | 2.7 VA |
| Current consumption | 11 mA |
| Electrical insulation class | Class II |
| Autonomy | 3 h |
| Charging time | 24 h |
| Luminous flux | Emergency condition: 90 lm |
| Material | Housing: plastic Cover: plastic |
| Device mounting | Flush Surface ceiling Surface wall |
| Height | 100 mm |
| Width | 331 mm |
| Depth | 46 mm |
| Product weight | 0.8 kg |
| Market segment | Small commercial |

Okolina

| | |
|---------------------------------------|--|
| IP degree of protection | IP42 |
| IK degree of protection | IK06 |
| ambient air temperature for operation | 0...40 °C |
| fire resistance | 850 °C |
| standards | EN 60598-2-22 IEC 50-11 IEC 695-2-1 EN 60695-2-10 |

Offer Sustainability

| | |
|---|---|
| Green Premium product | Green Premium product |
| Compliant - since 0833 - Schneider Electric declaration of conformity | Compliant - since 0833 - Schneider Electric declaration of conformity |

Informacije dane u ovoj dokumentaciji sadrže opće opise i/ili tehničke karakteristike o performansama ovdje sadržanih proizvoda. Ova dokumentacija nije namijenjena kao zamjena za niti bi se trebala koristiti za određivanje prikladnosti ili pouzdanosti predmetnih proizvoda za konkretne korisničke primjene. Svaki takav korisnik ili integrator dužan je provesti odgovarajuću i potpunu analizu rizika, procjenu i ispitivanje proizvoda u odnosu na odgovarajuću specifičnu primjenu ili uporabu istog. Niti društvo Schneider Electric Industries SAS niti bilo koje od njegovih povezanih poduzeća ili podružnica neće preuzeti obvezu ili snositi odgovornost za pogrešnu upotrebu ovdje sadržanih informacija.

Reference contains SVHC above the threshold - go to CaP for more details

Reference contains SVHC above the threshold

Available

Available

Available

Available

Contractual warranty

Warranty period

18 months
