

OVA38357

Exiway Easyled - znak izlaza u slučaju opas. - std. - u trajnom radu - 1h -240lm



Glavno

Range	Exiway
Aesthetic name	Exiway Easyled
Product or component type	Emergency light fitting
Device application	Lighting
Function	Standard
Supply	Non-maintained
Number of batteries	1 x 4.8 V 1.6 Ah Ni-Cd (Nickel-Cadmium)
Colour	White
Light source	LED integral LED 4 x 1 W
Light source colour	White
Cover type	Transparent
Wiring device additional information	Can be inhibited with rest mode via Teleur range of remote controls

Komplementarno

[Ue] rated operational voltage	220...230 V AC/DC at 50/60 Hz
Power consumption in VA	3.9 VA
Power consumption in W	1 W
Current consumption	16 mA
Electrical insulation class	Class II
Autonomy	1 h
Charging time	12 h
Luminous flux	Emergency condition : 240 lm
Type of glass	Serigraphed transparent glass
Material	Housing: plastic Cover: plastic
Device mounting	Surface ceiling Surface wall Flush false ceiling Flush wall
Height	37 mm
Width	292.5 mm
Depth	116.5 mm
Product weight	0.57 kg

Okolina

IP degree of protection	IP42
IK degree of protection	IK07
ambient air temperature for operation	5...30 °C
fire resistance	850 °C
product certifications	Aenor ENEC
standards	IEC 60695-2-10 EN/IEC 60598-2-22

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1231 - Schneider Electric declaration of conformity	Compliant - since 1231 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
